

22"

HIGH VELOCITY FAN



STANDARD
YM - YOKE MOUNT

ADDITIONAL MOUNTING OPTIONS:



RM Rack Mount **CW** Column-Wall **PS** Portable Stroller **PB** Pedestal Base
57 lbs 62 lbs 85 lbs 61 lbs

SHIPPING WEIGHT:

| SIZE | CFM | HP | FAN DIMENSIONS | | | AIR THROW DISTANCE | SHIPPING WEIGHT |
|------|------|-----|----------------|-----|-------|--------------------|-----------------|
| | | | W | D | ID | | |
| 22" | 5570 | 1/2 | 29" | 16" | 22.5" | 100' | 49 lbs |

FEATURES

Propeller: 21" Diameter, 3 Blade GalvAlum, 19°
Fan Inlet/Outlet: High Impact Polypropylene
Finger Guards: OSHA Compliant, Spiral Wound Steel
Power Cord (115V Only): 12' Length (Switch Optional)
RPM: 1725
Decibels: 66.5 @ 20' - 77.6 @ 3'
Coverage: 3600 ft²

Warranty: 2 Years

MOTOR

| MODEL | VOLTAGE | MOTOR RATED AMPS |
|-------|----------------|------------------|
| H22A | 115V/208-230V* | 6.0/3.0-2.9 |
| H22B | 208-230/460V | 2.4-2.3/1.2 |
| H22C | 277V | 1.85 |

Enclosure: TEAO Standard
Frame: 56
Ambient Temperature: 104°F
Duty Cycle: Continuous

*standard

